

# CORNELL URINAL

## 1.9Lpf / 0.5Gpf | WALL MOUNTED

□ 4810BEX Top Inlet

### PRODUCT SPECS

- High efficiency urinal
- 1.9Lpf / 0.5Gpf
- Vitreous china
- Washout flush action
- 3/4" Top inlet spud
- Outlet spud with 1/2" tubing tailpiece
- Flushing rim
- Mounting hardware supplied
- For concealed carrier installation
- Integral strainer
- Flushometer not included

### DIMENSIONS

321mm W x 324mm D x 457mm H

12 5/8" W x 12 3/4" D x 18" H

### COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- US EPA WaterSense  
*Please note: In order to comply with WaterSense certification this urinal must be used with 1.9Lpf / 0.5Gpf WaterSense labeled flushometer.*
- ASME A112.19.2 / CSA B45.1
- LEED Compliant

### SHIPPING

Cube 2.35  
GW 36 lbs



### TO BE SPECIFIED

Colour:

- Soft White

**NOTES:** Flush Valve is not included and must be ordered separately. Provide suitable reinforcement for all wall supports. Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Complies with ADA Section 4.18 when installed per code.

